

indexed_array

WMPRO, WMMINI FW >= 1.898 WMMEGA FW >= 2.0

Create an **array** of a specific type and size

Description

array indexed_array (int \$type, int \$size)

Create an indexed **array** with the specified type and number of elements. An indexed array is a more efficient way to store variables in memory if the size and data type is known beforehand. The **array()** function creates a hashed array, which consumes much more memory per element.

Parameters

\$type: 1=byte, 2=short, 3=int, 4=float

- Type 1: Array of bytes
- Type 2: Array of short integers (16 bits)
- Type 3: Array of 32 bit integers
- Type 4: Array of floating point numbers

\$size: The number of elements in the **array**

Return Values

Indexed **array**

Example

```
<?
$arr=indexed_array(1,100); // create an array of 100 bytes
?>
```

Note

There are no named keys in an indexed array, all elements are referenced by the index number. The first element is index=0, and the last element is index=\$size-1.

See Also

[array\(\)](#) - Create an **array**, with optional values

[uPHP Variable Types and Limits](#)

From:

<https://www.wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:

https://www.wattmon.com/dokuwiki/uphp/functions/indexed_array

Last update: **2021/09/13 05:57**

