

ini_get_array

WMPRO, WMMINI FW >= 1.0 WMMEGA FW >= 2.0

Get a group of parameters from an INI file as an **array**

Description

```
array ini_get_array ( string $filename [, string $section ] )
```

This function reads multiple configuration key/value pairs from an INI file.

Parameters

\$filename: Full path and name of the INI file

\$section: Optional, section inside the INI file

Return Values

If **\$section** is specified: a single-dimensional **array**, with all key/value pairs in the section.

If **\$section** is not specified: a two-dimensional **array** containing the entire INI file. The first dimension will contain the sections and the second the key/value pairs.

Loading an entire INI file can be memory intensive and should be avoided if the file has more than just a few elements. Instead, use [ini_get](#) to load specific values, which works well with large files. Or for fast access consider using NVRAM to store a large collection of data.

Example

Given that the file `/ini_get_array_example.ini` contains:

```
[settings]
name=John
age=33
```

... this code will read the entire INI file into `$arr` and display the contents:

```
<pre><?
  $arr=ini_get_array("/ini_get_array_example.ini");
  print_r($arr);
?></pre>
```

... and the output will be:

```
[$arr] = Array (  
[settings] = Array (  
    (string) [name] => John  
    (int) [age] => 33  
)  
)
```

See Also

[ini_get\(\)](#) - Get a value from an INI file

[ini_put_array\(\)](#) - Write a group of parameters to an INI file from an **array**

[ini_set\(\)](#) - Set a value in an INI file

From:

<http://www.wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:

http://www.wattmon.com/dokuwiki/uphp/functions/ini_get_array?rev=1492082308

Last update: **2021/09/13 05:56**

