ini_get_array

WMPRO, WMMINI FW >= 1.0 WMMEGA FW >= 2.0

Get a group of parameters from an INI file as an **array**

Description

array ini_get_array (string $filename [, string $section])

This function reads multiple configuration key/value pairs from an INI file.

Parameters

$filename: Full path and name of the INI file

$section: Optional, name of the section inside the INI file

Return Values

If the **section** is specified: a single-dimensional **array**, with all key/value pairs in the section.

If the **section** is not specified: a two-dimensional **array** containing the entire INI file. The first dimension will contain the sections and the second the key/value pairs.

Loading an entire INI file can be memory intensive and should be avoided if the file has more than just a few elements. Instead, use ini_get to load specific values, which works well with large files. Or for fast access consider using NVRAM to store a large collection of data.

Example

Given that the file /ini_get_array_example.ini contains:

```
[settings]
name=John
age=33
```

... this code will read the entire INI file into $arr and display the contents:

```
<pre><?
  $arr=ini_get_array("/ini_get_array_example.ini");
  print_r($arr);
?></pre>
```

... and the output will be:

```
[$arr] = Array (
[settings] = Array (
    (string) [name] => John
    (int) [age] => 33
)
)
```

See Also

ini_get() - Get a value from an INI file

ini_put_array() - Write a group of parameters to an INI file from an **array**

ini_set() - Set a value in an INI file

From:
http://www.wattmon.com/dokuwiki/ - **Wattmon Documentation Wiki**

Permanent link:
http://www.wattmon.com/dokuwiki/uphp/functions/ini_get_array?rev=1492091426

Last update: **2021/09/13 05:56**