

fclose

WMPRO, WMMINI FW \geq 1.0 WMMEGA FW \geq 2.0

Close a file, stream or socket

Description

`fclose (int $handle)`

Close a resource that has previously been opened

Parameters

handle: Valid handle of a previously opened resource

Return Value

None

Example

```
<?
  $f=fopen("/test.txt","r"); // open the file for reading and get the file
  handle
  if ($f) {
    print(fgets($f)); // print the first line of the file
    fclose($f); // close the file referenced by file handle
  } else {
    print("Unable to open file /test.txt");
  }
?>
```

See Also

[fopen\(\)](#) - Open a file for reading or writing

[f485open\(\)](#) - Open the RS-485 port at the specified baud rate and parity

[fseropen\(\)](#) - Open the serial port at the specified baud rate with optional parameters

[fsockopen\(\)](#) - Open an internet socket connection with optional timeout

[fread\(\)](#) - Return bytes from a file or stream

[fgets\(\)](#) - Return a single line from a file or stream, with optional size limit

[fwrite\(\)](#) - Write data to a file or stream

From:

<https://www.wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:

<https://www.wattmon.com/dokuwiki/uphp/functions/fclose?rev=1490632693>

Last update: **2021/09/13 05:56**

