

file_exists

WMPRO, WMMINI FW >= 1.0 WMMEGA FW >= 2.0

Check if a file exists

Description

```
int file_exists ( string $filename )
```

Return 1 (true) if the file exists, otherwise return 0 (false)

Parameter

\$filename: Full path and file name to check

Return Value

Integer: 1 if file exists, 0 if file does not exist

Examples

Simple existence report:

```
<pre><?
if (file_exists("/test.txt")) {
    print("File exists.");
} else {
    print("File does not exist!");
}
?></pre>
```

Create a new file with a unique non-conflicting filename - this example is extracted from the Wattmon OS "/scripts/logrotate.cgi":

```
<?
$date=strftime("/logs/log%Y%m%d.txt",time()); // desired filename, but it
may already exist
$cnt=0;
while (file_exists($date)) {
    $date=strftime("/logs/log%Y%m%d-$cnt.txt",time()); // unique non-
conflicting filename
    $cnt++;
}
```

```
    }
    $st="/logs/log.txt";
    if (file_exists($st)) {
        $res= rename($st,$date);
        if ($res==0) $_GLOBALS['sysmsg']="Log file rotated to ".$date;
        log("New logfile created after logrotate called.");
    } else {
        $_GLOBALS['sysmsg']="Unable to rotate, log file doesnt exist";
    }
    print("{\"status\":1,\"msg\":\"".$_GLOBALS['sysmsg']."\"}");
?>
```

See Also

[findfirst\(\)](#) - Start searching the current folder for files matching a pattern and attributes

[strftime\(\)](#) - Format the passed time using the format **string**

[time\(\)](#) - Return the current system timestamp

[rename\(\)](#) - Rename or move a file from source to destination

[log\(\)](#) - Print to the System Log

[uphp_special_variables](#) - Special arrays that are populated automatically (including `$_GLOBALS`)

From:

<https://www.wattmon.com/dokuwiki/> - **Wattpmon Documentation Wiki**



Permanent link:

https://www.wattmon.com/dokuwiki/uphp/functions/file_exists?rev=1491830535

Last update: **2021/09/13 05:56**