

ini_get

WMPRO, WMMINI FW >= 1.0 WMMEGA FW >= 2.0

Get a value from an INI file

Description

`mixed ini_get (string $filename, string $section, string $key, mixed $default)`

This function reads a configuration **key** value from an INI file. If the **section** and **key** are not found, the **default** value is returned.

Parameters

\$filename: Full path and name of the INI file

\$section: Name of the section inside the INI file

\$key: Name of the key inside the **section**

\$default: Value to be returned if the **section** and **key** are not found

Return Value

Mixed: Value associated with the **key**, or the **default** value if the **section** and **key** are not found

The value will be of type **string**, **integer** or **float** depending on the data type of the **default** value.

Example

Get the network mask from the Wattmon network configuration file

```
<?
  $val=ini_get("/config/network.ini","network","netmask","255.255.255.0");
  print($val);
?>
```

See Also

[ini_get_array\(\)](#) - Get a group of parameters from an INI file as an **array**

[ini_put_array\(\)](#) - Write a group of parameters to an INI file from an **array**

[ini_set\(\)](#) - Set a value in an INI file

From:

<https://www.wattmon.com/dokuwiki/> - Wattmon Documentation Wiki



Permanent link:

https://www.wattmon.com/dokuwiki/uphp/functions/ini_get?rev=1494253719

Last update: **2021/09/13 05:56**